# **RTS22** Wall switch QUIT Format 55

The RTS22 wall switch QUIT from the Format 55 series is a battery-operated Easywave transmitter with an acknowledge-button.

This complete version of the RTS22 wall switch contains all the components required to be put into operation immediately. The transmitter module, a white frame and a white single rocker with a acknowledge-symbol are included in the scope of delivery.

If necessary, the wall switch can be used in cover frames from other manufacturers (see compatibility list).

It can be used to acknowledge person calls or in care systems to acknowledge nurse calls.



### **Technical specifications**

| Coding  | Easywave  |
|---|---|
| Frequency   | 868.30 MHz  |
| Channels  | 1   |
| Range   | typically 150 m in good free-field conditions                               |
| Power supply  | 1x 3V-battery, CR2032   |
| Operation   | transmission lasts as long as the button<br>is pressed (maximum 36 seconds) |
| Operating temperature   | -20°C to +60°C  |
| Dimensions (W/L/H)<br>Mounting plate<br>Rocker<br>Cover frame | 71/71/1.8 mm<br>55/55/9.0 mm<br>80/80/9.4 mm                                |
| Weight  | 44g (including battery and cover frame)                                     |
| Color   | white similar RAL 9003  |
|   |   |

## Accessories (optional)



Single rocker QUIT RTS22-ACC-08

## Scope of delivery

- Transmitter module incl. batterv Rocker QUIT
- Cover frame
- Mounting plate
- · Adhesive pad
- Operating manual

## Accessories (optional)



| Models         |  |      |
|----------------|--|------|
| Product number | Description  |      |
| RTS22E5001B01  | Wall switch single rocker QUIT complete, Easywave, 1x PULSE,<br>Format 55, white |      |
|                |  |      |
| RADIO SYSTEMS: | Flexibility   Convenience   Energy efficiency   Secu                             | rity |

